

产品亮点

PRODUCT HIGHLIGHTS



经济高效 Economical & Efficient:

零并联电池组,无环流;

Zero parallel battery pack, no circulation;

设备效率最优拟合控制, 系统效率 > 90%。

The optimal fitting control of equipment efficiency > 90%.



安全可靠 Safe & Reliable :

Pack 内电芯级防火分区;

Fire compartment of battery cell in pack;

主动安全监测及灭火。

Active safety monitoring and fire extinguishing.



即插即用 Plug & Play :

一体化系统设计,即插即用;

Integrated system design, plug and play;

单柜自治控制, 支持多机并联。

Single cabinet autonomous control, support multi-machine parallel.



智慧友好 Smart & Friendly:

接入云平台, 远程监测;

Connect to cloud platform for remote monitoring;

智能无线,远程升级。

Smart wireless, remote upgrade.



215KWH 户外分布式储能系统(液冷)

215KWH OUTDOOR DISTRIBUTED ENERGY
STORAGE SYSTEM(LIQUID COOLING)



262KWH 户外分布式储能系统(液冷)

262KWH OUTDOOR DISTRIBUTED ENERGY
STORAGE SYSTEM(LIQUID COOLING)



钧灏电力·智能微网

+86 181 6895 7760

info@aipowertec.com

www.aipowertec.com

江苏省苏州市相城区平康路 6 号

SPECIFICATION PARAMETERS

规格参数

产品型号 Product Type	AI-ES215B	AI-ES262B
电池侧参数 Battery Side Parameters		
电芯类型 Cell Type	280 LFP	315 LFP
系统电池配置 System Battery Configuration	1P240S	1P260S
直流侧电池容量 DC Side Battery Capacity	215 kWh	262 kWh
电池电压范围 Battery Voltage Range	650V – 876V	650V – 949V
PCS 侧参数 PCS Side Parameters		
额定功率 Power Rating	100 kW	
额定电网电压 Rated Grid Voltage	400 V	
额定电网频率 Rated Grid Frequency	50 Hz / 60Hz (可设置)	
系统参数 System Parameter		
冷却方式 Cooling – Down Method	电池包液冷 Battery Pack Liquid Cooling	
尺寸 (长 x 宽 x 高) Size (Length x Width x Height)	930 * 1330 * 2300 mm	950 * 1350 * 2400 mm
防护等级 Levels of Protection	IP54	
认证证书 Certificates	GB / T 36276	

